









## SMART RANGE

### 1 MAIN FEATURES

**T** Triphasic  Diesel fuel  Perkins / 1103A-33G  Grupel / 184GB31  / 7320

**Hz** 50Hz  1500 r.p.m. **V** 400V **cos φ** 0,8

Standby power (STP)	33 kVA	26 kW
Prime Power (PRP)	30 kVA	24 kW
Power Continuous (COP)	- kVA	- kW

**Hz** 60Hz  1800 r.p.m. **V** 480V **cos φ** 0,8

Standby power (STP)	38 kVA	31 kW
Prime Power (PRP)	35 kVA	28 kW
Power Continuous (COP)	- kVA	- kW


#### OPEN SKID

Length (L)	1700 mm
Height (H)	1110 mm
Width (W)	850 mm
Weight	687 kg
Daily tank	150 L



#### SOUNDPROOF

Length (L)	1950 mm
Height (H)	1110 mm
Width (W)	800 mm
Weight	887 kg
Daily tank	40 L



	50Hz	60Hz
Acoustic pressure level @1m	-	-
Acoustic pressure level @7m	-	-

	50Hz	60Hz
Acoustic pressure level @1m	74 dB(A)	76 dB(A)
Acoustic pressure level @7m	61 dB(A)	63 dB(A)

#### AVAILABLE VOLTAGES - 50Hz

FP (cos Ø)	Phase	Voltage	COP (kVA/kW)	PRP (kVA/kW)	STP (kVA/kW)	Circuit breaker (A)
0,8	Three-phase	440	- / -	30 / 24	33 / 27	40
0,8	Three-phase	415	- / -	30 / 24	33 / 26	50
0,8	Three-phase	400	- / -	30 / 24	33 / 26	50
0,8	Three-phase	380	- / -	30 / 24	33 / 26	50
0,8	Three-phase	240	- / -	30 / 24	33 / 26	80
0,8	Three-phase	230	- / -	30 / 24	33 / 26	80
0,8	Three-phase	220	- / -	30 / 24	33 / 27	80
0,8	Single phase	240	- / -	19 / 15	20 / 16	80
1	Single phase	240	- / -	14 / 14	15 / 15	63
0,8	Single phase	230	- / -	19 / 15	20 / 16	80
1	Single phase	230	- / -	14 / 14	15 / 15	63
0,8	Single phase	220	- / -	19 / 15	20 / 16	100
1	Single phase	220	- / -	14 / 14	15 / 15	63

#### AVAILABLE VOLTAGES - 60Hz

FP (cos Ø)	Phase	Voltage	COP (kVA/kW)	PRP (kVA/kW)	STP (kVA/kW)	Circuit breaker (A)
0,8	Three-phase	480	- / -	35 / 28	38 / 31	50
0,8	Three-phase	460	- / -	35 / 28	38 / 30	50
0,8	Three-phase	440	- / -	34 / 28	38 / 30	50
0,8	Three-phase	416	- / -	34 / 27	38 / 30	50
0,8	Three-phase	240	- / -	35 / 28	38 / 31	100
0,8	Three-phase	230	- / -	35 / 28	38 / 30	100
0,8	Three-phase	220	- / -	34 / 28	38 / 30	100
0,8	Three-phase	208	- / -	34 / 27	38 / 30	100
0,8	Single phase	240	- / -	21 / 17	23 / 18	100
1	Single phase	240	- / -	20 / 20	22 / 22	100
0,8	Single phase	230	- / -	21 / 17	23 / 18	100
1	Single phase	230	- / -	20 / 20	22 / 22	100
0,8	Single phase	220	- / -	21 / 17	23 / 18	100
1	Single phase	220	- / -	20 / 20	22 / 22	100


## 2 ROOM INSTALLATION

EXHAUST SYSTEM	50 Hz			60 Hz		
	COP	PRP	STP	COP	PRP	STP
Exhaust gas temperature (°C)	-	500	520	-	520	530
Exhaust gas flow (m³/min)	-	5,7	5,8	-	6,4	6,6
Evacuated Heat (kW)	-	22	25	-	27	34
Maximum back pressure (kPa)	10					
Exhaust silencer attenuation (dB)	30					
Output Diameter (mm)	65					

VENTILATION SYSTEMS	50 Hz			60 Hz		
	COP	PRP	STP	COP	PRP	STP
Combustion air flow (m³/min)	-	2,16	2,15	-	2,6	2,57
Cooling airflow (m³/min)	53			70		
Maximum load losses (Pa)	125					
RADIATION	50 Hz			60 Hz		
	COP	PRP	STP	COP	PRP	STP
Engine (kW)	5	5	6	5	5	6
Alternator (kW)	3,4	3,4	3,8	4,0	4,0	4,4

## 3 ENGINE SPECIFICATIONS


GENERAL SPECIFICATIONS	50 Hz	60 Hz
Model	1103A-33G	
Emissions	Not satisfy 97/68/EC	
Performance grade	G2	
Operating method	Four stroke	
Fuel type	Diesel fuel	
Refrigeration system	Water/antifreeze Closed Circuit	
Aspiration system	Natural	
Injection system	Direct	
No. and Cylinder arrangement	3 In-Line	
Displacement (L)	3,3	
Cylinder bore (mm)	105	
Cylinder stroke (mm)	127	
Compression Ratio	19,25:1	
Regulation	Mechanic	
Rotation speed	1500	1800
Piston Speed (m/s)	6,4	7,62
Gross power COP (kWm)	-	-
Gross power PRP (kWm)	28,2	33,2
Gross power STP (kWm)	31	36,5
Fan power (kWm)	0,6	1,1
Net Power COP (kWm)	-	-
Net Power PRP (kWm)	27,7	32,2
Net Power STP (kWm)	30,4	35,4
BMEP COP (kPa)	-	-
BMEP PRP (kPa)	684	669
BMEP STP (kPa)	752	736



CONSUMPTION		50Hz		60Hz	
Fuel consumption	LOAD	lt/h	g/kWh	lt/h	g/kWh
STP	100%	8,1	222,1	9,5	219,2
	100%	7,2	217	8,6	218,1
	75%	5,6	225,5	6,6	223,2
PRP	50%	4,1	244,8	4,9	248,5
	100%	-	-	-	-
	75%	-	-	-	-
COP	50%	-	-	-	-
	50%	-	-	-	-
Oil consumption	< 0,15% of fuel consumption				
REFERENCE CONDITIONS					
Temperature (°C)	25				
Atmospheric pressure (kPa)	100				
CAPACITY					
Coolant (L)	10,2				
Oil (L)	8,3				
STARTING SYSTEM					
Voltage (V)	12				
Power (kW)	3				
Battery (Ah)	60				

## 4 ALTERNATOR SPECIFICATIONS

GENERAL SPECIFICATIONS	
Model	184GB31
Phases No.	Triphasic
Protection	IP23
Insulation	H
Temperature Rise	H
50Hz R.F.I. telephone interference	THF<2%
60Hz R.F.I. telephone interference	TIF<50
R.F.I. Suppression	BS EN 61000-6-2 /6-4, VDE 0875G, VDE 0875N.
Coupling	Semi-Flexible
Support	Single bearing



Wave form distortion with no load	< 1,5%
Wave form distortion with balanced linear load	< 5%
Winding Leads	12
Excitation (standard / option)	Self-excited / -
AVR Model (standard / option)	SX460/ -
Voltage Regulation (standard / option)	± 1,0%/ -



## SMART RANGE

RATED POWER - 50Hz								RATED POWER - 60Hz							
FP (cos Ø)	Phase	Voltage (V)	Power		Efficiency			FP (cos Ø)	Phase	Voltage (V)	Power		Efficiency		
			PRP/STP (kVA)	PRP/STP (%)	PRP/STP (%)	Xd	X'd				X''d	PRP/STP (kVA)	PRP/STP (%)	PRP/STP (%)	Xd
0,8	Three-phase	440	31 / 35	87,2 / 87,2	1,560	0,150	0,110	0,8	Three-phase	480	38 / 42	86,8 / 86,8	1,857	0,190	0,119
0,8	Three-phase	415	31 / 35	86,7 / 86,7	1,560	0,150	0,110	0,8	Three-phase	460	38 / 42	86,1 / 86,1	1,857	0,190	0,119
0,8	Three-phase	400	31 / 35	86,4 / 86,4	1,560	0,150	0,110	0,8	Three-phase	440	38 / 42	85,7 / 85,7	1,857	0,190	0,119
0,8	Three-phase	380	31 / 35	85,8 / 85,8	1,560	0,150	0,110	0,8	Three-phase	416	38 / 42	85,0 / 85,0	1,857	0,190	0,119
0,8	Three-phase	240	31 / 35	86,7 / 86,7	1,560	0,150	0,110	0,8	Three-phase	240	38 / 42	86,8 / 86,8	1,857	0,190	0,119
0,8	Three-phase	230	31 / 35	86,4 / 86,4	1,560	0,150	0,110	0,8	Three-phase	230	38 / 42	86,1 / 86,1	1,857	0,190	0,119
0,8	Three-phase	220	31 / 35	87,2 / 87,2	1,560	0,150	0,110	0,8	Three-phase	220	38 / 42	85,7 / 85,7	1,857	0,190	0,119
0,8	Single phase	240	19 / 20	85,3 / 85,3	1,560	0,150	0,110	0,8	Three-phase	208	38 / 42	85,0 / 85,0	1,857	0,190	0,119
1	Single phase	240	18 / 19	85,3 / 85,3	1,560	0,150	0,110	0,8	Single phase	240	21 / 23	85,3 / 85,3	1,857	0,190	0,119
0,8	Single phase	230	19 / 20	85,3 / 85,3	1,560	0,150	0,110	1	Single phase	240	20 / 22	85,3 / 85,3	1,857	0,190	0,119
1	Single phase	230	18 / 19	85,3 / 85,3	1,560	0,150	0,110	0,8	Single phase	230	21 / 23	85,3 / 85,3	1,857	0,190	0,119
0,8	Single phase	220	19 / 20	85,3 / 85,3	1,560	0,150	0,110	1	Single phase	230	20 / 22	85,3 / 85,3	1,857	0,190	0,119
1	Single phase	220	18 / 19	85,3 / 85,3	1,560	0,150	0,110	0,8	Single phase	220	21 / 23	85,3 / 85,3	1,857	0,190	0,119
								1	Single phase	220	20 / 22	85,3 / 85,3	1,857	0,190	0,119

## 5

## CONTROL PANEL



GENSET	DEEPSEA 7320	OPTIONAL
Voltage (Ph-Ph / Ph-N)	• / •	• / •
Current intensity	•	•
Frequency	•	•
RMS values	•	•
Generator phase sequence	•	•
Generator earth current [a]	o	o
No. of registers events	250	250
Real time clock	•	•
PIN protection	•	•
kWh, kVAr, kVAh, kVAh, cos Ø	•	•
Synchroscope (m)	-	o
Nº of available outputs [b]	6	6
Engine run hours	•	•
Indication of alarms on LCD	•	•
Total no. of LED indicators	12	12
No. of LED alarms	4	4
Sound signalling alarms	•	•
Scheduler	•	•
Fuel Level	•	•

Electrical network	DEEPSEA 7320	OPTIONAL
Voltage (Ph-Ph / Ph-N)	• / •	• / •
Current intensity [a]	-	o
Frequency	•	•
kVA, kW, cos Ø (a)	-	o
Inversion control between main-group	•	•
Protections and Alarms	DEEPSEA 7320	OPTIONAL
High / low battery voltage	A	o
Failure in Battery Charge Alternator	A	o
Failure to stop	A/S	A/S
Failure to start	A/S	A/S
Low fuel level	A/S	A/S
Overload	A/S	A/S
Earth leakage	A/S	A/S
Asymmetry between phases	A/S	A/S
Maintenance	A/S	A/S
High / Low generator frequency	A/S	A/S
Engine overspeed	A/S	A/S
Engine underspeed	A/S	A/S
Generator overvoltage	A/S	A/S
Generator undervoltage	A/S	A/S
ECU Alert (if applicable)	A/S	A/S
Low oil pressure	A/S	A/S
Low level of radiator water [f]	A/S	A/S
Engine high temperature	A/S	A/S
Fuel leakage/ theft	A	o

## 6 CONTROL PANEL

Engine	DEEPSEA 7320	OPTIONAL
Engine Speed	•	•
Low oil pressure protection	•	•
Oil pressure reading [c]	o	o
High temperature engine protection	•	•
Engine temperature reading [c]	o	o
Engine battery voltage	•	•
Intensity of the engine battery [d]	o	o
Fuel Consumption [e]	•	•
Low level of radiator water [f]	o	o
Engine maintenance scheduled	•	•
Communication	DEEPSEA 7320	OPTIONAL
USB female type B plug (Max. 6m) [g]	•	•
USB female type A plug (n)	-	o
RS232 port (Max. 15m) (n)	•	•
RS485 port (Max. 1,2Km) [h]	•	•
Ethernet port RJ45 [i]	o	o
GSM and/or GPS [j]	o	o
ModBus RTU protocol [h]	•	•
ModBus TCP protocol [i]	o	o
SNMP protocol [l]	o	o
CAN port (Max. 40m)	•	•
MSC port (Max. 240m) (m)	-	o
PLC functionality	•	•

Applications	DEEPSEA 7320	OPTIONAL
Automatic or manual starting	•	•
Remote start by NO dry contact	•	•
Automatic by mains failure	•	•
Alternating with timesharing	-	o
Multi-generators synchronization and load sharing (Max. 32 generators) (m)	-	o
Generator-Main in synchronism and load sharing (1 generator and 1 main) (m)	-	o
Optional expansions	DEEPSEA 7320	OPTIONAL
DSE2130 (8 inputs dig.)   IG-IOM (8 in/outputs dig. + 4 inputs anal.)   G-08 ( 8 inputs dig.)	•	•
DSE2157   I-RB8   G-06 (8 relay outputs)	•	•
DSE890   IL-NT-GPRS   G-GSM (GSM and/or GPS)	•	•
DSE891   IB-LITE   G-ETH (ethernet module)	•	•
DSE892   IB-LITE   - (ethernet module according SNMP protocol)	•	•
DSE2548   IGL-RA15   - (expansion with 8 additional LEDs)	•	•
DSE2510 / 20 (mirror controller, maximum distance 1km)	•	•
Standards		
Working temperature		-30 -> 70°C
Protection index (when assembled with sealing gasket)		IP65
Degree of humidity (during 48hr)		93% / 40°C

### Legend

•	Available
o	Optional
-	Not available
A	Warning Alarm
S	Stop alarm
[a]	Need additional CT
[b]	No. of outputs available for standard configuration. The outputs do not include relays and additional terminal connections.
[c]	If the information is not provided by the engine-ECU, you need an additional sensor

[d]	Needs additional ammeter
[e]	If information provided by the engine ECU
[f]	Required additional sensor
[g]	Requires the addition of the IL-NT-S-USB module
[h]	Requires the addition of the IL-NT-RS232-485 module
[i]	DeepSea: Requires the addition of the DSE891 module/ ComAp: Requires the addition of the IB-LITE module
[j]	DeepSea: Requires the addition of the DSE890 module/ ComAp: Requires the addition of the IL-NT-GPRS module
[l]	DeepSea: Requires the addition of the DSE892 module/ ComAp: Requires the addition of the IB-LITE module

Indicative weights and dimensions. Reference ambient conditions: 100kPa, 25°C, 30% relative humidity and fuel temperature below 40°C. Power in accordance with ISO 8528: Continuous power (PRP): Maximum available power to feed a variable electrical load for an unlimited period. The average of load factor in 24h of operation, shall not exceed 70% of the PRP. Admits 10% of overload during the maximum period of 1h every 12h of operation. The operation under overload shall not exceed 25h/year. Emergency Power (STP): Maximum available power to feed variable electrical load for a maximum period of 200h/year. The average of load factor in 24h of operation shall not exceed 70% of the STP. No overload. These specifications are subject to change without notice.

### Distribuidor