

INDUSTRIAL RANGE

1 MAIN FEATURES


T Triphasic
 Diesel fuel
 Iveco / C16 TE1W
 Grupel / 354GB600
 / 7320

Hz 50Hz	1500 r.p.m.	V 400V	cos φ 0,8
Standby power (STP)	660 kVA	528 kW	
Prime Power (PRP)	600 kVA	480 kW	
Power Continuous (COP)	- kVA	- kW	

Hz 60Hz	1800 r.p.m.	V 480V	cos φ 0,8
Standby power (STP)	686 kVA	549 kW	
Prime Power (PRP)	620 kVA	496 kW	
Power Continuous (COP)	- kVA	- kW	


OPEN SKID

Length (L)	4500 mm
Height (H)	2240 mm
Width (W)	1750 mm
Weight	3601 kg
Daily tank	1000 L



SOUNDPROOF

Length (L)	4500 mm
Height (H)	2240 mm
Width (W)	1750 mm
Weight	4674 kg
Daily tank	1000 L



	50Hz	60Hz
Acoustic pressure level @ 1m	-	-
Acoustic pressure level @ 7m	-	-

	50Hz	60Hz
Acoustic pressure level @ 1m	80 dB(A)	81 dB(A)
Acoustic pressure level @ 7m	70 dB(A)	71 dB(A)

AVAILABLE VOLTAGES - 50Hz

FP (cos φ)	Phase	Voltage	COP (kVA/kW)	PRP (kVA/kW)	STP (kVA/kW)	Circuit breaker (A)
0,8	Three-phase	440	- / -	563 / 450	619 / 495	800
0,8	Three-phase	415	- / -	600 / 480	660 / 528	1000
0,8	Three-phase	400	- / -	600 / 480	660 / 528	1000
0,8	Three-phase	380	- / -	597 / 478	660 / 528	1000
0,8	Three-phase	240	- / -	600 / 480	660 / 528	1600
0,8	Three-phase	230	- / -	599 / 480	660 / 528	1600
0,8	Three-phase	220	- / -	597 / 478	660 / 528	1600

AVAILABLE VOLTAGES - 60Hz

FP (cos φ)	Phase	Voltage	COP (kVA/kW)	PRP (kVA/kW)	STP (kVA/kW)	Circuit breaker (A)
0,8	Three-phase	480	- / -	620 / 496	686 / 549	800
0,8	Three-phase	460	- / -	618 / 495	683 / 547	800
0,8	Three-phase	440	- / -	617 / 494	682 / 546	1000
0,8	Three-phase	416	- / -	616 / 493	681 / 544	1000
0,8	Three-phase	240	- / -	620 / 496	686 / 549	1600
0,8	Three-phase	208	- / -	616 / 493	681 / 544	2000


2 ROOM INSTALLATION

EXHAUST SYSTEM	50 Hz			60 Hz		
	COP	PRP	STP	COP	PRP	STP
Exhaust gas temperature (°C)	-	557	-	-	554	-
Exhaust gas flow (kg/h)	-	-	2548	-	-	2853
Evacuated Heat (kW)	-	375,3	416,3	-	378,5	416,6
Maximum back pressure (kPa)	7					
Exhaust silencer attenuation (dB)	30					
Output Diameter (mm)	168					

VENTILATION SYSTEMS	50 Hz			60 Hz		
	COP	PRP	STP	COP	PRP	STP
Combustion air flow (m³/min)	-	43,8	-	-	49,9	-
Cooling airflow (m³/min)	631,8			783		
Maximum load losses (Pa)	196					
RADIATION	50 Hz			60 Hz		
	COP	PRP	STP	COP	PRP	STP
Engine (kW)	-	-	-	-	-	-
Alternator (kW)	20,4	20,4	27,5	29,4	29,4	32,3

3 ENGINE SPECIFICATIONS


GENERAL SPECIFICATIONS	50 Hz	60 Hz
Model	C16 TE1W	
Emissions	Not satisfy 97/68/EC	
Performance grade	G3	
Operating method	Four stroke	
Fuel type	Diesel fuel	
Refrigeration system	Water/antifreeze Closed Circuit	
Aspiration system	Turbocharged/intercooler	
Injection system	Common rail	
No. and Cylinder arrangement	6 In-Line	
Displacement (L)	15,9	
Cylinder bore (mm)	141	
Cylinder stroke (mm)	170	
Compression Ratio	16,5:1	
Regulation	Electronic	
Rotation speed	1500	1800
Piston Speed (m/s)	8,5	10,2
Gross power COP (kWm)	-	-
Gross power PRP (kWm)	516,8	546
Gross power STP (kWm)	570	601
Fan power (kWm)	11	22,9
Net Power COP (kWm)	-	-
Net Power PRP (kWm)	505,8	523
Net Power STP (kWm)	559	578
BMEP COP (kPa)	-	-
BMEP PRP (kPa)	2560	2270
BMEP STP (kPa)	2860	2500



CONSUMPTION		50Hz		60Hz	
Fuel consumption	LOAD	lt/h	g/kWh	lt/h	g/kWh
STP	100%	130,1	194	134,1	200
	75%	116,4	191	120,7	198
	50%	87,3	191	90,5	198
PRP	100%	59,1	194	62	203,5
	75%	-	-	-	-
	50%	-	-	-	-
COP	100%	-	-	-	-
	75%	-	-	-	-
	50%	-	-	-	-
Oil consumption	< 0,2% of fuel consumption				
REFERENCE CONDITIONS					
Temperature (°C)	40				
Atmospheric pressure (kPa)	100				
CAPACITY					
Coolant (L)	25,5				
Oil (L)	38				
STARTING SYSTEM					
Voltage (V)	24				
Power (kW)	5,5				
Battery (Ah)	155				

4 ALTERNATOR SPECIFICATIONS

GENERAL SPECIFICATIONS	
Model	354GB600
Phases No.	Triphasic
Protection	IP23
Insulation	H
Temperature Rise	H
50Hz R.F.I. telephone interference	THF<2%
60Hz R.F.I. telephone interference	TIF<50
R.F.I. Suppression	BS EN 61000-6-2 /6-4, VDE 0875G, VDE 0875N.
Coupling	Semi-Flexible
Support	Single bearing



Wave form distortion with no load	< 1,5%
Wave form distortion with balanced linear load	< 5%
Winding Leads	6
Excitation (standard / option)	Self-excited / PMG
AVR Model (standard / option)	KR440/MX341B
Voltage Regulation (standard / option)	± 1,0%/ ± 0,5%



INDUSTRIAL RANGE

RATED POWER - 50Hz

FP (cos Ø)	Phase	Voltage (V)	Power		Efficiency		
			PRP/STP (kVA)	PRP/STP (%)	Xd	X'd	X''d
0,8	Three-phase	440	563 / 619	95,1 / 95,1	2,778	0,148	0,108
0,8	Three-phase	415	600 / 660	94,9 / 94,9	2,778	0,148	0,108
0,8	Three-phase	400	600 / 660	95,8 / 94,8	2,778	0,148	0,108
0,8	Three-phase	380	600 / 660	94,5 / 94,5	2,778	0,148	0,108
0,8	Three-phase	240	600 / 660	94,9 / 94,9	2,778	0,148	0,108
0,8	Three-phase	230	600 / 660	94,8 / 94,8	2,778	0,148	0,108
0,8	Three-phase	220	600 / 660	94,5 / 94,5	2,778	0,148	0,108

RATED POWER - 60Hz

FP (cos Ø)	Phase	Voltage (V)	Power		Efficiency		
			PRP/STP (kVA)	PRP/STP (%)	Xd	X'd	X''d
0,8	Three-phase	480	720 / 792	94,9 / 94,9	3,215	0,155	0,105
0,8	Three-phase	460	720 / 792	94,6 / 94,6	3,215	0,155	0,105
0,8	Three-phase	440	720 / 792	94,4 / 94,4	3,215	0,155	0,105
0,8	Three-phase	416	720 / 792	94,2 / 94,2	3,215	0,155	0,105
0,8	Three-phase	240	720 / 792	94,9 / 94,9	3,215	0,155	0,105
0,8	Three-phase	208	720 / 792	94,2 / 94,2	3,220	0,160	0,110

5

CONTROL PANEL



GENSET	DEEPSEA 7320	OPTIONAL
Voltage (Ph-Ph / Ph-N)	• / •	• / •
Current intensity	•	•
Frequency	•	•
RMS values	•	•
Generator phase sequence	•	•
Generator earth current [a]	o	o
No. of registers events	250	250
Real time clock	•	•
PIN protection	•	•
kWh, kVAR, kVAh, kVArh, cos Ø	•	•
Synchroscope (m)	-	o
Nº of available outputs [b]	6	6
Engine run hours	•	•
Indication of alarms on LCD	•	•
Total no. of LED indicators	12	12
No. of LED alarms	4	4
Sound signalling alarms	•	•
Scheduler	•	•
Fuel Level	•	•

Electrical network	DEEPSEA 7320	OPTIONAL
Voltage (Ph-Ph / Ph-N)	• / •	• / •
Current intensity [a]	-	o
Frequency	•	•
kVA, kW, cos Ø (a)	-	o
Inversion control between main-group	•	•
Protections and Alarms	DEEPSEA 7320	OPTIONAL
High / low battery voltage	A	o
Failure in Battery Charge Alternator	A	o
Failure to stop	A/S	A/S
Failure to start	A/S	A/S
Low fuel level	A/S	A/S
Overload	A/S	A/S
Earth leakage	A/S	A/S
Asymmetry between phases	A/S	A/S
Maintenance	A/S	A/S
High / Low generator frequency	A/S	A/S
Engine overspeed	A/S	A/S
Engine underspeed	A/S	A/S
Generator overvoltage	A/S	A/S
Generator undervoltage	A/S	A/S
ECU Alert (if applicable)	A/S	A/S
Low oil pressure	A/S	A/S
Low level of radiator water [f]	A/S	A/S
Engine high temperature	A/S	A/S
Fuel leakage/ theft	A	o

6 CONTROL PANEL

Engine	DEEPSEA 7320	OPTIONAL
Engine Speed	•	•
Low oil pressure protection	•	•
Oil pressure reading [c]	o	o
High temperature engine protection	•	•
Engine temperature reading [c]	o	o
Engine battery voltage	•	•
Intensity of the engine battery [d]	o	o
Fuel Consumption [e]	•	•
Low level of radiator water [f]	o	o
Engine maintenance scheduled	•	•
Communication	DEEPSEA 7320	OPTIONAL
USB female type B plug (Max. 6m) [g]	•	•
USB female type A plug (n)	-	o
RS232 port (Max. 15m) (n)	•	•
RS485 port (Max. 1,2Km) [h]	•	•
Ethernet port RJ45 [i]	o	o
GSM and/or GPS [j]	o	o
ModBus RTU protocol [h]	•	•
ModBus TCP protocol [i]	o	o
SNMP protocol [l]	o	o
CAN port (Max. 40m)	•	•
MSC port (Max. 240m) (m)	-	o
PLC functionality	•	•

Applications	DEEPSEA 7320	OPTIONAL
Automatic or manual starting	•	•
Remote start by NO dry contact	•	•
Automatic by mains failure	•	•
Alternating with timesharing	-	o
Multi-generators synchronization and load sharing (Max. 32 generators) (m)	-	o
Generator-Main in synchronism and load sharing (1 generator and 1 main) (m)	-	o
Optional expansions	DEEPSEA 7320	OPTIONAL
DSE2130 (8 inputs dig.) IG-IOM (8 in/outputs dig. + 4 inputs anal.) G-08 (8 inputs dig.)	•	•
DSE2157 I-RB8 G-06 (8 relay outputs)	•	•
DSE890 IL-NT-GPRS G-GSM (GSM and/or GPS)	•	•
DSE891 IB-LITE G-ETH (ethernet module)	•	•
DSE892 IB-LITE - (ethernet module according SNMP protocol)	•	•
DSE2548 IGL-RA15 - (expansion with 8 additional LEDs)	•	•
DSE2510 / 20 (mirror controller, maximum distance 1km)	•	•
Standards		
Working temperature		-30 -> 70°C
Protection index (when assembled with sealing gasket)		IP65
Degree of humidity (during 48hr)		93% / 40°C

Legend

•	Available
o	Optional
-	Not available
A	Warning Alarm
S	Stop alarm
[a]	Need additional CT
[b]	No. of outputs available for standard configuration. The outputs do not include relays and additional terminal connections.
[c]	If the information is not provided by the engine-ECU, you need an additional sensor

[d]	Needs additional ammeter
[e]	If information provided by the engine ECU
[f]	Required additional sensor
[g]	Requires the addition of the IL-NT-S-USB module
[h]	Requires the addition of the IL-NT-RS232-485 module
[i]	DeepSea: Requires the addition of the DSE891 module/ ComAp: Requires the addition of the IB-LITE module
[j]	DeepSea: Requires the addition of the DSE890 module/ ComAp: Requires the addition of the IL-NT-GPRS module
[l]	DeepSea: Requires the addition of the DSE892 module/ ComAp: Requires the addition of the IB-LITE module

Indicative weights and dimensions. Reference ambient conditions: 100kPa, 25°C, 30% relative humidity and fuel temperature below 40°C. Power in accordance with ISO 8528: Continuous power (PRP): Maximum available power to feed a variable electrical load for an unlimited period. The average of load factor in 24h of operation, shall not exceed 70% of the PRP. Admits 10% of overload during the maximum period of 1h every 12h of operation. The operation under overload shall not exceed 25h/year. Emergency Power (STP): Maximum available power to feed variable electrical load for a maximum period of 200h/year. The average of load factor in 24h of operation shall not exceed 70% of the STP. No overload. These specifications are subject to change without notice.

Distribuidor